

GENERAL CONTROLLERS



SZ-7510T | Temperature Controller with Power Switch

SZ-7569T | Temperature Controller with Power Switch and 20A Relay


TOUCH SENSITIVE KEYPAD

Dimension : 36x78mm


Panel Cutout : 29x71mm

FEATURES	SZ-7510T	SZ-7569T
Display: n° digits	2x17mm 7 segment display & 5 LEDs for Indication	2x17mm 7 segment display & 5 LEDs for Indication
Power supply	230VAC Standard. Others on request.	230VAC Standard. Others on request.
Temperature Range	-40°C to +99°C	-40°C to +50°C
Probe inputs		
Thermostat	NTC	NTC
Relay Outputs		
Compressor	8(3)A	20(8)A
Alarm		
Others		
Buzzer		
Serial Output		

SZ-7510T



SZ-7569T



**Coming
Soon**

SZ-7510T



SZ-7589T



GENERAL / ANTIFREEZE CONTROLLERS



SZ-7510-P-DI | Temperature Controller with Digital Input

SZ-7512-P | Antifreeze Control with Manual Reset

SZ-7514-P | Antifreeze & Temperature Controller


SZ-7515-P | Temperature Controller with Buzzer

Dimension : 34.5x75mm


Panel Cutout : 29x71mm

FEATURES	SZ-7510-P-DI	SZ-7512-P	SZ-7514-P	SZ-7515-P
Display: n° digits	2x14.2mm(0.56")LED	2x14.2mm(0.56")LED	2x14.2mm(0.56")LED	2x14.2mm(0.56")LED
Power supply	230VAC Standard. Others on request.	230VAC Standard. Others on request.	230VAC Standard. Others on request.	230VAC Standard. Others on request.
Temperature Range	-50°C to +99°C	-50°C to +50°C	-50°C to +50°C	-50°C to +99°C
Probe inputs				
Thermostat	NTC	NTC	NTC	NTC
Antifreez			NTC	
Digital inputs				
HP / LP / OSS / Phase Loss / Digital Door I/P	Yes			
Relay Outputs				
Compressor	8(3)A	8(3)A	8(3)A	8(3)A
Compressor2				
Alarm				
Others				
Buzzer		Yes	Yes	Yes
Serial Output				


SZ-7510-P-DI




SZ-7512-P



SZ-7514-P



SZ-7515-P



WALL MOUNT / BLOOD BANK CONTROLLERS



Dimension : 34.5x75mm
Panel Cutout : 29x71mm




Dimension : 126x80mm


SZ-7510-WV	Temperature Controller with Wall Mount
SZ-7510-C	Temperature Controller with PC Communication
SZ-7516-P	Blood Bank Controller
SZ-7571	Temperature Controller with Analog Output

FEATURES	SZ-7510-WV	SZ-7510-C	SZ-7516-P	SZ-7571
Display: n° digits	3x14.2mm(0.56")LED	3x14.2mm(0.56")Dot Matrix	2x14.2mm(0.56")LED	3x14.2mm(0.56")LED
Power supply	230VAC Standard. Others on request.	230VAC Standard. Others on request.	10VAC Standard. Others on request.	100-265VAC 50-60Hz Others on request.
Temperature Range	-40.0°C to 50.0°C	-50.0°C to 50.0°C	-50°C to +99°C	-40.0°C to 50.0°C
Probe inputs				
Thermostat	NTC	NTC	NTC	NTC
Defrost (Coil)				
Analog Outputs				
4-20mA				Yes
0-10V				Yes
Relay Outputs				
Compressor	8(3)A	8(3)A	8(3)A	8(3)A
Compressor2				
Alarm				
Others				
Buzzer			Yes	
Serial Output		RS485		
Battery Backup			Yes (upto 24 Hrs.)	


SZ-7510-WV



SZ-7510-C



SZ-7516-P



SZ-7571

